

Specification	Symbol	Condition / Comment	FQD 30-06 UF	FQD 30-08 UF	Unit
Maximum Operating Voltage	$V_{O(max)}$	$I_{off} < 100 \mu ADC$ , $T_{case} = 25^{\circ}C$	3600	3000	VDC
Maximum Isolation Voltage	$V_i$	Between HV switch and control / GND, continuously	>10000		VDC
Typical Breakdown Voltage	$V_{Br}$	$I_{off} > 1 \text{ mADC}$ , $T_{case} = 70^{\circ}C$	3960	3250	VDC
Maximum Turn-On Peak Current	$I_{P(max)}$	$T_{case} = 25^{\circ}C$ Peak current is internally limited	60	80	ADC
Maximum Off-State Current	$I_{off}$	$T_{case} = 25^{\circ}C$ , $0.8 \times V_{O(max)}$ , Lower $I_{off}$ on request	10		$\mu ADC$
Output Impedance	$Z_{out}$	Standard devices see option M-RS	75		Ohm
Maximum Continuous Power Dissipation	$P_{d(max)}$	Standard devices & FC, $T=25^{\circ}C$ Devices with option DLC/ILC, $T_{liquid}=25^{\circ}C$ , 1liter/min With Option GCF, $T_{flange}=25^{\circ}C$	5 60-200 (consult Behlke) 200		Watt
Max. Continuous Switching Frequency	$f_{(max)}$	Cooling may be required at higher operating frequency Standard devices with Option HFS supply Customized units	100 150 up to 500		kHz
Maximum Burst Frequency	$f_{b(max)}$	Use option HFB for >10 pulses within 20 $\mu s$ or less	2		MHz
Operating Temperature Range	$T_o$	Extended range on request	-40...75		$^{\circ}C$
Storage Temperature Range	$T_{ST}$		-50...90		$^{\circ}C$
Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch	25		mT
Max. Auxiliary Voltage	$V_{aux}$	Built-in overvoltage limiter (replaceable)	5		VDC
Typical Power Dissipation	$P_d$	@ $0.8 \times V_o$ $C_L$ Pockels cell capacitance Data valid for cooling option GCF. Standard device without cooling option have 10% less losses.	f=2kHz $C_L=10 \text{ pF}$ 1.98 f=20kHz $C_L=5 \text{ pF}$ 16.02 $C_L=10 \text{ pF}$ 19.44 $C_L=20 \text{ pF}$ 23.04 f=100kHz $C_L=10 \text{ pF}$ 97.2	3.6 30 36.96 39.12 184.8	Watt
Typical Turn-On Jitter	$t_{j(on)}$	$V_{aux} / V_{tr} = 5 \text{ DC}$	100		ps
Typical Propagation Delay Time	$t_{d(on)}$	Resistive load, $0.1 \times I_{P(max)}$ , $0.8 \times V_{O(max)}$ , 50-50%	50		ns
Typical Output Pulse Jitter	$t_j$	Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 \text{ VDC}$	1		ns
Typical Turn-On Rise Time	$t_{r(on)}$	- @ $0.8 \times V_o$ Standard - Standard Output impedance 75 Ohm - Pockels cell connecting leads <100mm (4")	$C_L=5 \text{ pF}$ 1.2 $C_L=10 \text{ pF}$ 1.4 $C_L=20 \text{ pF}$ 1.8	1.5 1.8 2.3	ns
Typical Turn-On Time	$t_{on}$	Switch on-time only. See also option OT-xxxx	100		ns
Effective HV Pulse Width	$t_{p(HV)}$	$C_L=10 \text{ pF}$ , top flatness<3%. See also option M-RL	200		ns
Typical HV Pulse Fall Time	$t_f$	10-90%, $C_L=10 \text{ pF}$ . See also Option M-RL.	1.2		$\mu s$
Switch recovery time	$t_{rc}$	Driver recovery only. Trigger pulse $t_p=100 \text{ ns}$	500		ns
Maximum Number of Pulses / Burst	$N_{(max)}$	@ $f_{b(max)}$ Standard Option I-HFB Option HFB	150 >1000 >10000	Use option HFB for >150	Pulses
Coupling Capacitance	$C_C$	HV side against control side	10		pF
Auxiliary Supply Voltage Range	$V_{aux}$	The +5 V supply is not required in the HFS mode.	5		VDC
Typical Auxiliary Supply Current	$I_{aux}$	$V_{aux} = 5.00 \text{ VDC}$ , $T_{case} = 25^{\circ}C$ .	$0.01 \times f_{(max)}$ 70 400	80 400	mADC
Fault Signal Output		Indicates over temperature, over frequency (>100kHz) and low aux. voltage (>4.75 V) "Ready" = H "Fault" = L	4.5 0.8		VDC
Trigger Signal Voltage Range	$V_{TR}$	3-6 VDC recommended for low jitter	2-10		VDC
Minimum trigger pulse width	$t_{pr(min)}$	Switching behaviour cannot be influenced by trigger pulse	50		ns
Fault Signal Output Current		Source/sink current, short circuit proof	10		mADC
Dimensions	LxWxH	Standard housing Devices with option GCF, non-isolated cooling fins Devices with option DLC	79x38x18 Please contact the manufacturer!		mm <sup>3</sup>
Weight		Standard housing Devices with option CCF, non-isolated cooling fins Devices with option DLC	Please contact the manufacturer!		g
Control Signal Input Logic GND / 5V Return 5V Auxiliary Supply Fault Signal Output LED Indicators Temperature Protection		<b>Pin 1 / Yellow.</b> TTL compatible with Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V recommended for low jitter). <b>Pin 2 / Black.</b> The ground pin is internally connected with the safety earthing terminal (threaded insert) on bottom side. <b>Pin 3 / Red.</b> The 5 V input is used for rep rates up to the specified max. frequency $f_{(max)}$ . Higher rep rates require option HFS. <b>Pin 4 / Orange.</b> TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault. <b>Pin 5 / Black.</b> The ground pin is internally connected with the safety earthing terminal (threaded insert) on bottom side. <b>GREEN:</b> "Ready, auxiliary power good". <b>YELLOW:</b> "Switch triggered". <b>RED:</b> "Fault condition, switch OFF" <b>A)</b> Standard switches and switches with option GCF: Thermo trigger $75^{\circ}C$ , response time < 60 s @ $3 \times P_d(max)$ , $\Delta T=25K$ (50 to $75^{\circ}C$ ). Separate driver protection. <b>B)</b> Switches with option DLC: $65^{\circ}C$ , response time < 3 s @ $3 \times P_d(max)$ , $\Delta T=25K$ (40 to $65^{\circ}C$ ), coolant flow > 3l / min. Separate driver protection.			
FQD 30-06 UF	Q-Switch driver, on mode, 3.0 kVDC, 60 A	Option OFF	OFF mode configuration.	Option OT-10 $\mu$	Switch on-time 10 $\mu s$
FQD 30-08 UF	Q-Switch driver, on mode, 3.0 kVDC, 80 A	Option NEG	Negative high voltage supply/negative output pulse polarity.	Option OT-100 $\mu$	Switch on-time 100 $\mu s$
		Option HFB	High Frequency Burst. Improved burst capability by driver.	Option PL-HV	Plug connector for high voltage connection
		Option HFS	High Frequency Switching (two auxiliary supply inputs V1 & V2)	Option SPT-C	Shielded pigtail for control connection, incl. LEMO plug
		Option UL94	Flame retardant casting resin according to UL94-VO	Option GCF	Grounded cooling flange (attachment on heatsinks)
		Option M-RL	Modified working resistor (customized HV-pulse, $t_p(HV)$ & $f$ )	Option ILC	Indirect Liquid Cooling (for water). $P_{d(max)}$ can be increased by the factor 3 to 15.
		Option M-RS	Modified damping resistor (customized HV-pulse, tr)	Option DLC	Direct Liquid Cooling (for FPE/PFC). $P_{d(max)}$ can be increased by the factor 10
		Option OT-1 $\mu$	Switch on-time 1 $\mu s$		

FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE.